

NovaFlex® Sweeper & Vacuum Truck Hoses

Debris Collection/ Boom Hose

Nova-Vac™ 5049BG Boom Hose

Heavy duty corrugated vacuum hose. Corrugated outer cover for ease of handling. Designed for full vacuum boom applications. Smooth inner tube for enhanced material flow. Abrasion resistant tube for extended wear.

Construction:

Tube: Black smooth abrasion resistant rubber. Available in RG and YG. Reinforcement: Helix wire and textile. Cover: Black abrasion resistant rubber. Length: Standard lengths and made to order. Temperature: -40°F (-40°C) to +160°F (+71°C)



I.D."	O.D."	Part No.	MBR"	Vac Hg	Length"	Wt lbs./ft.
2½	3.36	5049BG-02500-00	9	29	50, 100'	2.90
3	2.86	5049BG-03000-00	11	29	50, 100'	3.40
4	4.87	5049BG-04000-00	15	29	50, 100'	4.60
6	6.70	5049BG-06000-00	22	29	50, 100'	5.30
6	6.70	5049BG-06000-00-103	22	29	103"	5.30
6	6.70	5049BG-06000-00-240	22	29	240	5.30
8	8.80	5049BG-08000-00	30	29	50	7.20
8	8.80	5049BG-08000-00-060	30	29	60	7.20
8	8.80	5049BG-08000-00-062	30	29	62	7.20
8	8.80	5049BG-08000-00-66	30	29	66	7.20
8	8.80	5049BG-08000-00-72	30	29	72	7.20
8	8.80	5049BG-08000-00-103	30	29	103	7.20
8	8.80	5049BG-08000-00-120	30	29	120	7.20
8	8.80	5049BG-08000-00-127	30	29	127	7.20
8	8.80	5049BG-08000-00-240	30	29	240	7.20
10	11.11	5049BG-10000-00	60	29	20, 25, 50'	10.9



Nova-Vac™ 5053YG Tapered Connector Sleeve

Designed to meet O.E.M.'s specifications for serviceability. This abrasion resistant smooth tube with full vacuum tapered sleeve is used to connect different size piping on vacuum truck applications for sound dampening and vibration elimination.

Construction:

Tube: Novawear YG smooth abrasion resistant rubber
 Reinforcement: Helix wire and textile
 Cover: Black abrasion resistant rubber
 Length: Standard lengths and made to order
 Temperature: -40°F (-40°C) to +160°F (+71°C)
 Also available in Black standard Novawear BG tube



I.D."	Part No.	Length"	Vacuum
8 x 10	5053YG-08000-00	10	29 Hg
9½ x 12	5053YG-09625-00	10	29 Hg
10 x 12	5053YG-10000-00	10	29 Hg

Nova-Vac™ 5052BG Straight Connector Sleeve

Designed to meet O.E.M.'s specifications for serviceability. This abrasion resistant smooth tube and full vacuum sleeve is used to connect different size piping on vacuum truck applications for sound dampening and vibration elimination.

Construction:

Tube: Black smooth abrasion resistant rubber
 Reinforcement: Helix wire and textile
 Cover: Black abrasion resistant rubber
 Length: Standard lengths and made to order
 Temperature: -40°F (-40°C) to +160°F (+71°C)




I.D."	Part No.	Length"	Vacuum
6	5052BG-08000-98-010	10	29 Hg
8	5052BG-09625-98-010	10	29 Hg
10	5052BG-10000-98-010	10	29 Hg

NovaFlex HDAP All Purpose Thermoplastic Rubber Hose

Heavy duty thermoplastic inner tube with fully encapsulated plastic, external wear strip. All extruded thermoplastic heavy wall hose. Designed for medium duty material handling where flexibility is paramount. Good chemical and temperature resistance with smooth interior for superior product flow.

Construction:

Material: Thermoplastic rubber
 Diameters: 2" (51 mm) to 8" (203 mm)
 Weight: 3"(76 mm) = 1.4 lbs./ft (.635k)
 Length: Diameters 2"(51 mm) to 4" (102 mm), 100ft (30.48 m) lengths;
 Diameters 5"(127 mm) to 8" (203 mm), 50ft (15.24 m) lengths
 Temperature range: -65°F (-54°C) to +160°F (+71°C)



I.D."	O.D."	Part No.	WP(psi)	Vacuum	Bend Radius	Wt./Ft.
2	2.77	9SFHDAPO2	40	29 Hg	2.5	0.97
4	4.67	9SFHDAPO4	30	29 Hg	12	1.80
6	6.85	9SFHDAPO6	30	28 Hg	18	3.50
8	8.99	9SFHDAPO8	30	27 Hg	20	5.65