

Leaf and Debris / Collection Hose

Nova-Green™ Urethane Hose

A lightweight urethane alternative to cumbersome PVC hose. Designed specifically for the landscaping market. Nova-Green all urethane tube provides superior abrasion resistance and excellent flexibility. The hose features a smooth interior with a uniform .045" wall gauge for even abrasion resistance throughout. The exposed rigid helix allows the hose to drag easily across surfaces when the hose is fully charged while providing protection to the hose wall.

Applications:

Terra-seeding, Bark Blowing
Mulch Blowing

Construction:

Material: UV stabilized urethane wall, rigid plastic helix
Diameters: 2" (51 mm) to 6" (152 mm)
Lengths: 50ft (15.24) and 100ft (30.48 mm)
Temperature range: -50°F (-45°C) to 200°F (+93°C)
Color: Clear wall with green helix



I.D."	Part No.	Length	WP (PSI)	Vacuum
2	9NFNOVAGREEN02	50', 100'	35	30 Hg
3	9NFNOVAGREEN03	50', 100'	30	30 Hg
4	9NFNOVAGREEN04	50', 100'	21	30 Hg
5	9NFNOVAGREEN05	50' 100'	18	23 Hg
6	9NFNOVAGREEN06	50'	16	23 Hg

NovaFlex™ TPU Heavy Duty Urethane Vacuum Hose

All extruded construction, lightweight alternative to cumbersome rubber hose. Designed specifically for transfer of abrasive materials under vacuum.

Applications:

Dewatering, material transfer and suction, debris collection

Construction:

Material: Extruded polyurethane wall, rigid PVC helix
Diameters: 4" (102 mm), 6" (152 mm), 8" (203 mm)
Weight: 6" diam. = 2.5lbs/ft
Lengths: 50 ft lengths
Temperature range: -50°F (-46°C) to +200°F (+93°C)
Colour: Extruded Transparent Blue TPU
Rated for full vacuum. Available with copper static wire



I.D."	Part No.	Length	Wall	Vacuum
4	9SFTPUXFV04	50'	0.06	29 Hg
6	9SFTPUXFV06	50'	0.06	29 Hg
8	9SFTPUXFV08	25'	0.06	25 Hg

Nova-Vac™ 5063BG Leaf / Debris Hose

Designed to meet O.E.M.'s specifications for serviceability. This highly flexible, internally and externally corrugated vacuum hose has a high abrasion resistant rubber tube with 4" (102 mm) soft cuffs on each end for easy installation.

Construction:

Tube: Black corrugated abrasion resistant rubber
Reinforcement: Helix wire and textile
Cover: Black corrugated abrasion resistant rubber
Temperature range: -40°C (-40°C) to 160°F (+71°C)



I.D."	Part No.	Length	Vacuum
12	5063BG-12000-00-048	48	4 Hg
12	5063BG-12000-00-100	100	4 Hg
12	5063BG-12000-00-120	120	4 Hg
12	5063BG-12000-00-144	144	4 Hg
14	5063BG-14000-00-048	48	4 Hg
14	5063BG-14000-00-100	100	4 Hg
14	5063BG-14000-00-120	120	4 Hg
14	5063BG-14000-00-144	144	4 Hg
16	5063BG-16000-00-048	48	4 Hg
16	5063BG-16000-00-100	100	4 Hg
16	5063BG-16000-00-120	120	4 Hg
16	5063BG-16000-00-144	144	4 Hg
18	5063BG-18000-00-120	120	4 Hg

NovaFlex™ SF-TPU .045 thou wall Urethane Leaf Collector Hose

An economical alternative to cumbersome rubber hose. Polyurethane wall for superior abrasion resistance.

UV stabilized for outdoor use. Lightweight, good flexibility, smooth interior for optimum flow. Encapsulated wire helix.

Applications:

Leaf collection equipment
Medium duty material handling
Plant debris collection

Construction:

Material: 0.045" translucent blue urethane, encapsulated wire
Diameters: 2" (51 mm) to 18" (457.2 mm)
Weight: 6" (152 mm) = 1.4 lbs/ft (.635 k), 8" (203 mm) = 1.9 lbs/ft (.86 k)
Lengths: Up to 8" (203 mm) diameters 25ft (7.62 m) & 50ft (15.24 m)
10" (254 mm) diameters and up 25ft (7.62 m)
Compression Ratio: 2:1
Temperature range: -65°F (-54°C) to +200°F (+93°C)
Colour: Blue with blue wear strip.
Also available in black & clear; minimum quantity required.
*Available in 0.060" gauge clear 8" (203 mm) to 14" (356 mm) diameter.



I.D."	Part No.	Length	Wall	Vacuum
6	9SFTPUW06HW	25', 50'	0.045	23 Hg
8	9SFTPUW08HW	25', 50'	0.045	13 Hg
10	9SFTPUW10HW	25'	0.045	6 Hg
12	9SFTPUW12HW	25'	0.045	5 Hg
14	9SFTPUW14HW	25'	0.045	5 Hg
16	9SFTPUW16HW	10', 12', 25'	0.045	2 Hg
18	9SFTPUW18HW	10', 12', 25'	0.045	1 Hg

